



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 111, DN none
Ordering No. 11148-PE24

Description

| | |
|-------------|---|
| Flange | ISO-F 250 |
| Actuator | pneumatic, double acting – with position indicator |
| Feedthrough | Bellows |

Technical data

| | | |
|--|--|--|
| Leak rate | – Valve body – Valve seat | $< 1 \cdot 10^{-9}$ mbar ls ⁻¹ $< 1 \cdot 10^{-9}$ mbar ls ⁻¹ |
| Pressure range | | $1 \cdot 10^{-8}$ mbar to 1.2 bar (abs) |
| Differential pressure on the gate | | ≤ 1.2 bar |
| Differential pressure at opening | | ≤ 30 mbar |
| Conductance (molecular flow) | | 21 690 ls ⁻¹ |
| Cycles until first service | | 200 000 (unheated and under clean conditions) |
| Temperature (Maximum values: depending on operating conditions and sealing materials) | – Valve Body – Actuator – Solenoid valve – Position indicator | ≤ 150 °C (bake-out max. 24h) ≤ 120 °C ≤ 50 °C ≤ 80 °C |
| Heating and cooling rate | | 50 °C h ⁻¹ |
| Material (main components) | – Valve Body – Mechanism – Bellows – Bushing | AISI 304 (1.4301) AISI 316L (1.4404), AISI 304 (1.4301) AISI 316L (1.4404, 1.4435) Hydrocarbonate |
| Seal | – Bonnet – Gate – Actuator | FKM (Viton®) FKM (Viton®), O-ring FKM (Viton®), NBR |
| Mounting position | | any |
| Volume of pneumatic actuator | | 0.35 l / 0.0122 ft ³ |
| Compressed air min. – max. overpressure | | 5 – 7 bar / 73 – 102 psi |
| Compressed air connection | | G $\frac{1}{8}$ " (1/8" NPT for USA) |
| Actuation time | – closing – opening | 4 s 4 s |
| Weight | | 51 kg / 112 lbs |
| Behavior in case of compressed air pressure drop | – Valve closed – Valve open | valve remains closed undefined |
| Behavior in case of power failure | – Valve closed – Valve open | depending on customer installation depending on customer installation |

| | | |
|-------------------|--------------------------|------------------|
| Created by: SCHMC | Release date: 23.03.2021 | 1/2 |
| Modified by: | Release date: | 1082055EA |

