



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet No. 258488EB

HV Angle Valve, Series 264, DN 40 (ID 1 1/2 ")

Ordering No. 26432-KA12 or 26432-KE12

### Description

Flanges	ISO-KF40
Actuator	- pneumatic, single acting with opening spring - without solenoid - without position indicator
Feedthrough	Bellows

### Technical data

Leak rate	- body & valve seat	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
Molecular flow conductance		45 ls <sup>-1</sup>
Pressure range		$1 \cdot 10^{-8}$ mbar to 5 bar, abs
Differential pressure on the plate:		
- in opening direction		≤ 2 bar
- in closing direction		≤ 5 bar
Differential pressure at opening		≤ 1 bar in either direction
Closing time		≤ 0,75 sec.
Admissible temperature	- valve body, actuator	0°C - 120°C
Cycles until first service		3 million (T <sub>max</sub> 80°C, differential pressure max. 1 bar)
Material:		
	- valve body	<b>26432-KA12</b> Aluminum (AlMgSi)
	- pneumatic actuator	Aluminum
	- valve plate	AISI 316L
	- bellows	AISI 316L (1.4404)
	- bonnet & plate seal	Viton
	- actuator o-rings	Viton
		<b>26432-KE12</b> Stainless Steel (AISI 304)
		Aluminum
		AISI 316L
		AISI 316L (1.4404)
		Viton
		Viton
Weight		1,21 kg / 2.668 lbs      1,37 kg / 3.020 lbs
Mounting position		any
Volume of air cylinder		0,035 l / 0,0012 ft <sup>3</sup>
Compressed air pressure for pneumatic		4 - 8 bar / 60 - 115 psi
Compressed air connection		M5 female (option others)

Created by: C. Baur	Release date: 2005.03.15	Page 1 of 1
Modified by::	Release date:	<b>258488EB</b>